

Ductile Iron Fittings DN 80 - DN 750

Derwent Industries has a wide range of ductile iron fittings available, all of which can be supplied either coated in Rilsan / Nylon 11 or black cement lined. Rilsan makes it unnecessary to wrap the fittings (unless otherwise directed by asset owner) and less susceptible to corrosion.

Derwent Industries prides itself on customer service and being able to provide the required ductile iron fitting configuration to suit our customer's requirements. This may include specially manufactured bends to certain angles or variety of end connection or tapping alternatives.

Material Specifications:

Size Range:	DN 80 - DN 750
Coating:	Rilsan / Nylon 11 or Black Cement Lined
Material:	Ductile Iron
Standard:	AS/NZS 2280 (where applicable)
Product License No.:	1989 (where applicable)
Pressure Rating:	PN16, PN35, PN16 Light weight



Range Includes:

• **Note:** The following list identifies only part of the range of fittings available and products are available in various configurations. All fittings are manufactured to Derwent Industries tolerances as per our standards certification:

- | | | | |
|-------------|-----------------|--------------|----------------|
| • Bends | • Washout Bends | • Connectors | • Adaptors |
| • Gibaults | • Tapers | • Tees | • Scour Tees |
| • Hydrants | • Risers | • Crosses | • Caps & Plugs |
| • Bellmouth | • Wye Junctions | • Flanges | • Collars |

